



## PR-RAIL GATE

### Features:

- Self-closing operation.
- Post, wall or in-line mounting.
- Supplied with 1.5 metre aluminium rail.
- Economical single gate can swing inward or outward.
- Adjustable spring tension.
- Aluminium rails include hi-vis reflective tape.

PART No.	DESCRIPTION
PRG1500-PA	PR-Rail gate assembly
KIT23	Gate to post fixing kit – Up to 63mm diameter posts
KIT24	Gate to post fixing kit – Up to 90mm diameter posts
PR-RAK	PR-Rail in-line gate adaptor kit
C63SME	Surface mount bollard – 63.5 x 1.6 x 1000mm
C63BGE	Below ground bollard – 63.5 x 1.6 x 1000mm
C90SM	Surface mount bollard – 90 x 5 x 1000mm
C90BG	Below ground bollard – 90 x 5 x 1000mm

**Description:** Self-closing pedestrian gate.

**Compatibility:** Designed for the PR-Rail system.

**Material:** Mild steel and aluminium.

**Finish:** Galvanised or powder coated Yellow.

**Rail type:** Single aluminium extrusion 145 x 40mm.

**Operation:** Push open/adjustable spring assisted closure.

**Gate swing:** 90 degrees.

**Gate stop:** Built-in.

**Opening:** Single gate operation.

**Max. open:** 1.5 metres.

**Min. open:** No minimum.

**Adjustment:** Length of rail can be cut down on site.

**Height:** Top rail 1000mm above floor.

**Clearance:** Overhead clearance not applicable.

**Mounting:** Post, wall or in-line.

**Weight:** 6.3kgs gate assembly with 1.5 metre rail.

