



RUBBER WHEEL STOP


An economical one piece rubber wheel stop with Hi-Vis Yellow panels. Manufactured from recycled materials with dimensions that comply to AS/NZS 2890.1:2004.

Suited to use in factories, warehouses and car parks etc. Comes complete with fixings.

Features:

- Complies with AS/NZS 2890.1:2004.
- Economical and simple to install.
- Solid moulded construction.
- Recycled materials won't chip or corrode.
- · Comes complete with fixings.

Material:	Recycled and natural rubber.
Finish:	Solid Black rubber with Hi-Vis Yellow Panels.
Length:	1650mm.
Width:	155mm.
Height:	95mm.
Weight:	14kgs.
Fixings:	3 x 150mm masonry anchors (gravel spikes optional).



PART No.	DESCRIPTION
RWS1650	One piece rubber wheel stop — Black (fixings supplied)
SPIKES	Optional steel gravel spikes for fixing into loose surfaces – 300 x 12mm each



WHEEL STOP SIGNS

Features:

- Made from flexible polypropylene.
- Range of standard lengths.
- Can be custom made.
- "Do-It-Yourself" blank sign available.
- · Will accept vinyl lettering.
- Can be attached to most wheel stop designs.

Material:	1.4mm White polypropylene.
Finish:	Screen printed text. Black text – CWS-VISITOR, CWS-STAFF, CWS-15MIN, CWS-RESERVED. Blue text – CWS-DISABLED.
Size:	75 x 450 x 1.4mm.
Fixings:	6 x self tapping screws (supplied).
Installation:	Install onto Compliance and Rubber wheel stop ranges (CWS1700 & RWS1650).



PART No.	DESCRIPTION
CWS-VISITOR	Wheel stop sign — VISITOR
CWS-DISABLED	Wheel stop sign — DISABLED
CWS-STAFF	Wheel stop sign — STAFF
CWS-15MIN	Wheel stop sign -15 MINUTE
CWS-RESERVED	Wheel stop sign – RESERVED
CWS-BLANK	Wheel stop sign — BLANK